

ATM Fuses

Mini blade-type fuse

- Color-coded for easy identification
- Visible indication of blown condition
- Tin-plated connector blades for corrosion resistance



Specifications

Interrupting Capacity	1,000A
Voltage Max. Operating	32V DC

PN	Amps	Pack
5270	5A	2
5271	10A	2
5272	15A	2
5273	20A	2
5274	30A	2
5286	5A, 10A, 15A, 20A, 30A	5

ATO or ATC Fuses

Fast-acting blade fuse

- Color-coded for easy identification
- Visible indication of blown condition
- Tin-plated connector blades for corrosion resistance



Specifications

Interrupting Capacity	1,000A
Voltage Max. Operating	32V DC

PN	Amps	Pack	PN	Amps	Pack
5235	1A	2	5235100	1A	25
5236	2A	2	5236100	2A	25
5237	3A	2	5237100	3A	25
5238	4A	2	5239100	5A	25
5239	5A	2	5240100	7.5A	25
5240	7.5A	2	5241100	10A	25
5241	10A	2	5242100	15A	25
5242	15A	2	5243100	20A	25
5243	20A	2	5244100	25A	25
5244	25A	2	5245100	30A	25
5245	30A	2			
5246	40A	2			
5287	5A, 10A, 15A, 20A, 25A, 30A	6			

Related Products



Fuse Holders



ST-Blade Fuse Blocks



SafetyHub Fuse Blocks

easyID ATC Fuses

Fast-acting easyID illuminated blade fuses use Light Emitting Diode (LED) technology to show when a fuse has blown.

- Color-coded for easy identification
- Visible indication of blown condition
- Tin-plated connector blades for corrosion resistance



Specifications

Interrupting Capacity	1,000A
Voltage Max. Operating	32V DC

PN	Amps	Pack
5291	3A	2
5292	5A	2
5293	7.5A	2
5294	10A	2
5295	15A	2
5296	20A	2
5297	25A	2
5298	30A	2
5299	40A	2
5290	3x 3A, 3x 5A, 3x 7.5A, 3x 10A, 6x 15A, 3x 20A, 3x 25A, 3x 30A, 3x 40A	30

5290

Related Products



Fuse Holders



ST-Blade Fuse Blocks

MAXI Fuses

Provides economical branch circuit protection

- Color-coded for easy identification
- Silver-plated connector blades for corrosion resistance
- Visible indication of blown condition



Specifications

Interrupting Capacity	1,000A
Voltage Max. Operating	32V DC

PN	Amps	Pack
5138	30A	1
5139	40A	1
5140	50A	1
5141	60A	1
5142	70A	1
5143	80A	1

Related Products



MAXI Fuse Block



MAXI In-Line Fuse Holder

AMI or MIDI Fuses

Compact fuse for main or branch
30A to 200A circuit protection

- Color-coded for easy identification
- Visible indication of blown condition
- Tin-plated connector blades for corrosion resistance



Specifications

Interrupting Capacity	5,000A @ 16V DC 2,000A @ 32V DC
Voltage Max. Operating	32V DC

Regulatory

Meets SAE J1171 external ignition protection requirements when used with Fuse Blocks
IP66 – protected against powerful water jets



PN	Amps	Color	Pack
5250	30A	Orange	2
5251	40A	Green	2
5252	50A	Red	2
5253	60A	Yellow	2
5254	70A	Brown	2
5255	80A	White	2
5256	100A	Blue	2
5257	125A	Pink	2
5258	150A	Lt Blue	2
5259	175A	Tan	2
5260	200A	Purple	2

Related Products




Safety Fuse Block 7720

MEGA or AMG Fuses

Economical fuse for 100A to
300A circuit protection

Specifications

Interrupting Capacity	2,000A @ 32V DC
Voltage Max. Operating	32V DC
Trip Time Delay	



Regulatory

Meets SAE J1171 external ignition protection requirements When used with Safety Fuse Block 7721
IP66 – protected against powerful water jets



PN	Amps	Pack
5101	100A	1
5102	125A	1
5103	150A	1
5104	175A	1
5105	200A	1
5107	250A	1
5108	300A	1

Related Products



MEGA or AMG Fuse Block



Safety Fuse Block 7721

MRBF Fuses

MRBF—Marine Rated Battery Fuse Space-saving ignition protected fuse for 30 to 300 Amp loads. Must use with MRBF Fuse Blocks

- Color-coded for easy identification
- Visible indication of blown condition



Specifications

Interrupting Capacity	10,000A @ 14V DC 5,000A @ 32V DC 2,000A @ 58V DC
Voltage Max. Operating	58V DC
Fuse Hole Opening	M8 (5/16")
Trip Time Delay	



Regulatory

Meets SAE J1171 external ignition protection requirements
IP66 – protected against powerful water jets

PN	Amps	Color	Pack
5175	30A	LT Green	1
5176	40A	LT Blue	1
5177	50A	Red	1
5178	60A	Gold	1
5180	75A	Brown	1
5181	80A	Lime	1
5182	90A	Purple	1
5183	100A	Yellow	1
5184	125A	Green	1
5185	150A	Orange	1
5186	175A	White	1
5187	200A	Blue	1
5189	250A	Pink	1
5190	300A	Gray	1



Related Products



MRBF Fuse Blocks

Class T Fuses

High interrupt capacity for large battery banks including Lithium-Ion and TPPL batteries

- Extremely fast short-circuit response
- Recommended by most inverter manufacturers



Specifications

Interrupting Capacity 20,000A @ 125V DC
Voltage Max. Operating 125V DC

Regulatory

UL listed to standard 248-15

PN	Amps	Pack
5112	110A	1
5113	125A	1
5114	150A	1
5115	175A	1
5116	200A	1
5117	225A	1
5118	250A	1
5119	300A	1
5120	350A	1
5121	400A	1

ANL Fuses

For 35A to 750A circuit protection



- Silver-plated connector blades for corrosion resistance
- Visible indication of blown condition

Specifications

Interrupting Capacity 6,000A @ 32V DC
Voltage Maximum 32V DC

Regulatory

35-500A ONLY – Meets SAE J1171 external ignition protection requirements



PN	Amps	Retail Pack	PN	Amps	Pack
5164	35A	1	5129	200A	1
5165	40A	1	5131	250A	1
5122	50A	1	5133	300A	1
5123	60A	1	5135	350A	1
5124	80A	1	5136	400A	1
5125	100A	1	5137	500A	1
5126	130A	1	Not Ignition Protected		
5127	150A	1	5161	600A	1
5128	175A	1	5163	750A	1

Related Products



Class-T Fuse Blocks

Related Products



ANL Fuse Blocks